

## RTR12 Series

Features	Benefits
<b>American made</b>	American made means better quality & parts availability. Most tillers are imported.
<b>Tractor hp range*</b>	15-40 hp
<b>42" &amp; 50"</b>	20-50 hp
<b>58" &amp; 60"</b>	25-60 hp
<b>74"</b>	30-60 hp
<b>82"</b>	
<b>Reverse tilling action</b>	Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.
<b>3 Year gearbox warranty</b>	3 Years on housing, seals, & bearings. Shows our confidence in the product.
<b>10 Year limited warranty on sprockets and roller chain</b>	Shows our confidence in this product providing many years of service.
<b>42", 50", 58", 66", 74", &amp; 82" Working widths</b>	A wide range of widths are available to meet specific customer needs.
<b>6 1/2" Digging depth</b>	For deep soil penetration.
<b>Bent plate steel upper hitch</b>	Plate steel is stronger than flat bar type hitch.
<b>Clevis lower hitch</b>	Provides additional strength and easy one person hook-up.
<b>Offset Capabilities</b>	Allows tiller to work closer to objects such as fence lines, buildings and trees.
<b>Fits Land Pride Quick Hitch</b>	Allows for quick and easy one person hook-up. (Offset cannot be used with Quick Hitch.)
<b>Parking stand</b>	Allows for easy hook-up and storage.
<b>Adjustable skid shoes</b>	Control depth with seven adjustments.
<b>Formed and reinforced rear deflector</b>	Keeps dirt in and leaves a level finish. Forming gives deflector additional strength. Adjustable deflector allows for various finish results.
<b>Front deflector</b>	Front deflector is flexible to take the beating from rocks or debris.
<b>Bolt in rotor</b>	Rotor removes and replaces easier for servicing.
<b>15" Rotor swing diameter</b>	For deep tilling and turns the soil over faster.
<b>4 'C' shaped heat-treated tines per flange</b>	"C" Shaped tines require less hp to move through the ground. Four tines requires less horsepower than 6 tines.
<b>Double lip seal on rotor bearing</b>	Double lip seal helps keep the dirt out and the grease in.
<b>Fully shielded slip-clutch driveline</b>	Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.
<b>#80 Drive chain enclosed in oil bath</b>	Heavy drive chain stretches less, and oil bath keeps wear to a minimum.
<b>Stamped chaincase cover</b>	Stamped forming gives the chain cover strength.
<b>Optional BX/B driveline</b>	This driveline will fit BX and B Kubota tractors without cutting it to fit.

## RTA12 Series

Features	Benefits
<b>American made</b>	American made means better quality & parts availability. Most tillers are imported.
<b>Tractor hp range</b>	15-40 hp 20-50 hp 25-60 hp 30-60 hp
<b>42" &amp; 50" 58" &amp; 60" 74" 82"</b>	
<b>3 Year gearbox warranty</b>	3 Years on housings, seals, bearings. Shows our confidence in the product.
<b>10 Year limited warranty on sprockets and roller chain</b>	Shows our confidence in this product providing many years of service.
<b>42", 50", 58", 66", 74", &amp; 82" Working widths</b>	A wide range of widths are available to meet specific customer needs.
<b>6 1/2" Digging depth</b>	For deep soil penetration.
<b>Formed plate steel upper hitch</b>	Plate steel is stronger than flat bar type hitch.
<b>Clevis lower hitch</b>	Provides additional strength and easy one person hook-up.
<b>Offset Capabilities</b>	Allows tiller to work closer to objects such as fence lines, buildings and trees.
<b>Fits Land Pride Quick Hitch</b>	Allows for quick and easy one person hook-up. Does not offset to the left with Quick Hitch.
<b>Parking stand</b>	Allows for easy hook-up and storage.
<b>Adjustable skid shoes</b>	Control depth with various settings.
<b>Formed and reinforced rear deflector</b>	Forming gives deflector additional strength. Adjustable deflector allows for various finish results.
<b>Bolt in rotor</b>	Rotor removes and replaces easier for servicing.
<b>15" Rotor swing diameter</b>	For deep tilling and turning the soil over faster.
<b>4 'C' Shaped heat-treated tines per flange</b>	"C" Shaped tines require less hp to move through the ground. Four tines requires less horsepower than 6 tines.
<b>Double lip seal on rotor bearing</b>	Double lip seal helps keep the dirt out and the grease in.
<b>Fully shielded slip-clutch driveline</b>	Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.
<b>#80 Drive chain enclosed in oil bath</b>	Heavy drive chain stretches less, and oil bath keeps wear to a minimum.
<b>Stamped chaincase cover</b>	Stamped forming gives the chain cover strength.
<b>Optional BX/B driveline</b>	This driveline will fit BX and B Kubota tractors without cutting it to fit.