

Wanco® Portable Diesel Light Towers



WANCO® The industry leader.

800-972-0755
www.wanco.com



**Working late?
Light up your job site with Wanco® Diesel Light Towers.**

Not just another light tower, Wanco Diesel Light Towers use state-of-the-art technology to achieve the most efficient illumination, shining a uniform light pattern across the entire job site.

Other advancements include a choice of low-speed engines that provide trouble-free diesel performance and greater longevity, and unsurpassed engine accessibility via a maintenance panel that lifts completely out of the way.

See our complete line of light towers at wanco.com.

Get over 30 years of Wanco ingenuity in our portable diesel light towers.

Light fixtures

High-output fixtures feature a high-intensity parabolic reflector that increases illumination and creates a brighter, more uniform light pattern. The result is greater visibility and improved safety for workers. For fast job-site setup and less downtime, each light fixture can be aimed independently without the use of tools—and the fixtures stay in place once positioned.

Tower

The telescoping tower is compact when stored, yet extends to 30 feet when deployed. Two winches raise and extend the mast easily. Power- and hand-operated winches are available. In the upright position, the light tower mast rotates 360 degrees and the lights operate at any height, preventing the trailer from having to be moved frequently.

Power system

Trouble-free performance and greater longevity are achieved with a choice of rugged, low-RPM, Tier 4 Final diesel engines and high-quality four-pole generators. A 30-gallon fuel tank provides extended run times of 60 to 70 hours between refueling. The rugged, translucent polyethylene fuel tank is rupture resistant and offers an instant view of fuel level, eliminating the need for a fuel gauge.

Serviceability

Wanco has created a unique innovation that greatly improves serviceability. For complete access to the engine, generator and electrical components, Wanco Diesel Light Towers feature a hinged top panel that rises with the mast when maintenance is required. No other light tower makes engine access this easy. The gull-wing side doors may be opened while the maintenance panel is raised, further enhancing access.



Hinged top panel opens fully. The light tower mast attaches to the panel for maintenance and raises the panel using the drawbar winch.



Engine and components are easily accessible with top panel up. Crossbar can be removed and side doors can be opened with panel raised.

Specifications

Physical

Deployed footprint	112 x 127 in. (285 x 321 cm), W x L
Operating height	Max. 30 ft. (9.14m) Min. 12½ ft. (3.81m)
Travel height	66 in. (168cm)
Operating weight	1800 lbs. (815kg)
Shipping weight	1580 lbs. (717kg)
Tires	ST175/80D13
Tow hitch	Combo-type for 2-inch ball and 3-inch pintle hook

Power system

Engine type	Tier 4 Final diesel, 3-cylinder, 4-cycle
Engine speed	1800 rpm
Generator type	Brushless
Generator insulation	H
Battery	12 V dc, 550 CCA
Maximum power output	12.1 or 13.6 hp (9 or 10 kW)*
Displacement	56 or 68 cu. in. (916 or 1123cm ³)*
Sound level	71 dB at 23 feet (7m) at max. load
Fuel tank capacity	30 gal. (114L)
Fuel consumption	0.44 gal./hr. (1.67L/h)
Runtime before refueling	60 to 70 hrs., approx.

Lights

Lamps	Four metal halide lamps
Wattage	1000 watts per lamp
Fixtures	Elipsical housing with glass cover

Output power

Output	6 kW
Voltage	120 V or 240 V*
Amperage	50 A @ 120 V, 25 A @ 240 V
Frequency	60 Hz or 50 Hz*
Voltage regulation	±5%, no load to full load

Functional

Steel enclosure protects components from the elements. Enclosure is powder-coated, lockable, and weather-resistant.

Control panel includes elapsed hour meter, convenience outlet for powering external equipment, and circuit breakers for on/off functionality and protection.

Diesel engine includes glow-plug preheat system for increased service life and improved cold-weather starting.

Automatic engine shutdown system protects engine from damage due to low oil pressure and high coolant temperature.

For maintenance, hinged top panel provides unimpeded access to engine, generator, and electrical components.

Options include a choice of engines, 7.5 or 8 kW generator, auto-start/stop system, 120- and 240-volt power receptacles, block heater, fuel/water separator, and electric winches. Vertical-tower and LED models are also available.

**Depending on model*

Due to Wanco's commitment to continuous improvement of our products, all information is subject to change without notice. Wanco and the Wanco logo are registered trademarks of Wanco Inc. All other trademarks are property of their respective owners.



WANCO INC.
5870 Tennyson Street
Arvada, Colorado 80003
800-972-0755
303-427-5700
303-427-5725 fax
www.wanco.com